


raptor



ANDROID



4K DISPLAY



MULTI-TOUCH



SEAMLESS EXPERIENCE



SCREEN CAST



20W x 2 SPEAKERS



INTERACTIVE FLAT PANEL (IFP)



WHITEBOARD

CLOUD INTEGRATION

ANTI-GLARE

PLAY STORE

SPLIT SCREEN

E-SHARE

PALM DETECTION

RAPTOR PRODUCT SPECIFICATION

Display	Screen Size & Model No.	65 INCH & RPBI65
	Bonding Technology	Zero Bonding
	Response Time	6.5ms
	Aspect Ratio	16:9
	Max Visual Area (H/V) (mm)	1428.48×803.52
	Resolution (H/V)	4K UHD 3840×2160
	Pixel Pitch (mm)	0.372×0.372
	Refresh Rate	60Hz
	Display Color	1.07B (10bit)
	Color Gamut NTSC(Typ.)	72%
	Contrast Ratio(Typ)	4000:1
	Viewing Angles (H/V)	178°
	Back Light Unit	DLED
	Brightness	350 nits
Panel Life	≥50000 hours	
Android OS	System Version	Android 14.0
	Solution	V100
	Frequency	1.2GHZ
	CPU	8 Core A55
	GPU	Quad-core Mali G52 MP4
	RAM	8GB
	ROM	128GB
	Languages	English, Thai, Vietnamese, Korean, Portuguese, Russian, Indonesian, Polish, Ukrainian, Japanese, Spanish, French, German, Italian, Dutch, Arabic, Kazakh, Simplified Chinese, Traditional Chinese
Touch	Touch Technology	Infrared Touch
	Supporting Systems	Windows 10/8/7/XP/ Android/Linux/Mac OS X/Chrome
	Touch Point	40 Points Touch
	Min. Object Size	2mm
	Interactivity	Simultaneous Pen and Touch
	Response Time	≤5ms
	Touch Precision	±1mm
	Touch Height	≤3mm
	Writing Mode	Single Pen with Two Colors
	Touch Resolution	32767 (W) ×32767(D)
	Glass	Anti-glare Tempered Glass

Wireless	Bluetooth	Version	5.0
		Working Frequency	2.4GHz
		Working Dist.	0~10m
		Type	Built-in Bluetooth
	Wi-Fi	Version	Wi-Fi 5 (802.11a/b/g/n/ac)
		Working Frequency	2.4GHz/5GHz
		Working Distance	0~10m
		Type	Built-in Wi-Fi
Audio & Video	Speaker	Soundtrack & Power	2.0 2×20W
	Camera	Pixel	48MP Ai Camera
		Qty(s).	1
		Location	Front Up
		Viewing Angle	DFOV:119°, HFOV:97°, VFOV:74°
	Microphone	Pick-up Dist.	0~8m
		Qty(s).	8 array mic
		Pick-up Angle	0°~180°
		Features	Supports voice tracking, 2D/3D noise suppression
	Connectivity	Front Interfaces	Type-C x1, USB 3.0 x 2, USB-B TOUCH 2.0 x1, HDMI IN x1
Rear Interfaces		RS232 x 1, PC TOUCH x 1, HDMI IN(ARC) x 1, RJ45 IN x 1, USB 2.0 x 2, TF Card x1, COAX x 1, AUDIO OUT x 1	
Power	Voltage		100~240V, 50/60Hz
	Max. Power Consumption		280W
	Standby Power Consumption		≤0.5W
Mechanical	Product Dimensions (L×W×D)		1484.30×919.9×116mm
	Packing Dimensions (L×W×D)		1630×220×1050mm
	Thickness		146mm
	VESA Wall Mount (L×W)		500×400mm
	Wall Screw		M8×20mm
	Product Weight		40±1kgs
	Packing Weight		50±1kgs
	Environmental	Working Temperature	
Working Humidity		10%~90%RH	
Storage Temperature		-20°C~60°C	
Storage Humidity		10%~90%RH	
Working Altitude		<5000m	

Accessories	Power Cable	×1 (1.5m)
	HDMI Cable	×1 (1.5m)
	Touch Cable	×1 (1.5m)
	Remote Control	×1
	Stylus Pen	×2
	Telescope Pointer	×1
	Wall Mount Bracket	×1

Available on



Efficient • Transpaent • Inclusive

www.raptorbiz.com